SPIRE X28 PRO

Discharge Beam moving head 280 w

The **Spire X28 Pro** is a stilish moving head beam in a very compact and lightweight housing. It delivers high light output and even coverage field. It features an High quality 280W Lamp. The lamp equips with the reflector built-in, providing perfect lamp alignment. The moving head features ultra sharp beam effect with low consumption. The fixture is integrated with a full complement of professional characteristics including a static gobo wheel, color wheel, 8 and 16-Facet prism, Prism morphing effect, frost filter, motorized linear focus, variable speed shutter/strobe, linear dimmer, color time and gobo time controllable. and special rotating 8 colour filter The fixture supports DMX, RDM (Remote Device Management).
The fixture’s exterior housing is beautifully balanced basing on a modern design philosophy with supremely harmonious interior structure for remarkable control. The sculpted body of the Spire X28 Pro achieves more than just a striking look. The 2*1/4 turn fastening omega clamps, available for vertical and horizontal plug-in, make installations fast and easy.It’s applicable for large scale live concerts, TV productions, road shows, clubs, etc.









PRODUCT DETAILS

Key features

- 280 w Lamp 7800°K Life span2000H Philips MSD Platinum 14R Lamp
- 2° Beam Angle
- Smooth linear mechanical dimming
- 0-20Hz high speed strobe effect with variable speed
- Color wheel with 14 dichroic colors plus open with half colour
- Static gobo wheel with 17 gobos plus open
- Frost filter system (Hybrid effect for wash)
- 8 and 16 Facet prism with variable speed and directions
- Prism morphing effect
- 7 colour multiray effect filter
- PAN and TILT with 8/16 bit scanning, photoelectric reset and automatic error correction
- DMX512 with RDM / Master-Slave / Auto / Sound modes
- High Efficient low noise self adjusting fan cooling system
- 2.4" High resolution TFT LCD display with easy user-interface

Specifications

Lamp	280 w Lamp 7800°K Life span2000H Philips MSD Platinum 14R Lamp
Lamp life	2000 hours
Input voltage	AC100-240V 50/60Hz
Power consumption	430 W
Control Mode	DMX512, Master/slave, Sound, Auto Mode, RDM
DMX Channel Modes	16/20 Channel
Beam angle	2°
Dimmer	Dual flag mechanical dimming system
Focus	High resolution motorized
X/Y Scan	Smooth and precise 16 Bit 540°PAN and 270°TILT
Strobe	0-20T/sec high speed
Display	2.4" TFT LCD display with 4 control buttons
Colors	Rotating wheel with 11 colors plus open
Gobos	Static wheel with 17 Gobos plus open
Prism	8-facet with variable speed and direction
Prism	16-facet with variable speed and direction
Effect	Prism morphing effect between them
Special Effect	7 colour multiray effect filter
Frost	Wash filter with hybrid effect
Front lense	Anti-reflection 136mm
Housing	Flame-retardant plastic
Internal Running Temperature	0 ÷ 40°C
Dimensions (WxDxH)	316,8(W)*235(D)*519(H)mm
Weight	12 kg
Package Dimensions (WxDxH)	365(W)*360(D)*520(H)mm
Package Weight	14,3 kg