

SPIRE X28 PRO

Discharge Beam moving head 280 w

The **Spire X28 Pro** is a stylish moving head beam in a very compact and lightweight housing. It delivers high light output and even coverage field. It features an High quality 280W Lamp. The lamp equips with the reflector built-in, providing perfect lamp alignment. The moving head features ultra sharp beam effect with low consumption. The fixture is integrated with a full complement of professional characteristics including a static gobo wheel, color wheel, 8 and 16-Facet prism, Prism morphing effect, frost filter, motorized linear focus, variable speed shutter/strobe, linear dimmer, color time and gobo time controllable. and special rotating 8 colour filter The fixture supports DMX, RDM (Remote Device Management). The fixture's exterior housing is beautifully balanced basing on a modern design philosophy with supremely harmonious interior structure for remarkable control. The sculpted body of the Spire X28 Pro achieves more than just a striking look. The 2*1/4 turn fastening omega clamps, available for vertical and horizontal plug-in, make installations fast and easy. It's applicable for large scale live concerts, TV productions, road shows, clubs, etc.



PRODUCT DETAILS

Key features

280 w Lamp 7800°K Life span2000H Philips MSD Platinum 14R Lamp

2° Beam Angle

Smooth linear mechanical dimming

0-20Hz high speed strobe effect with variable speed

Color wheel with 14 dichroic colors plus open with half colour

Static gobo wheel with 17 gobos plus open

Frost filter system (Hybrid effect for wash)

8 and 16 Facet prism with variable speed and directions

Prism morphing effect

7 colour multiray effect filter

PAN and TILT with 8/16 bit scanning, photoelectric reset and automatic error correction

DMX512 with RDM / Master-Slave / Auto / Sound modes

High Efficient low noise self adjusting fan cooling system

2.4" High resolution TFT LCD display with easy user-interface

Specifications

Lamp	280 w Lamp 7800°K Life span2000H Philips MSD Platinum 14R Lamp
Lamp life	2000 hours
Input voltage	AC100-240V 50/60Hz
Power consumption	430 W
Control Mode	DMX512, Master/slave, Sound, Auto Mode, RDM
DMX Channel Modes	16/20 Channel
Beam angle	2°
Dimmer	Dual flag mechanical dimming system
Focus	High resolution motorized
X/Y Scan	Smooth and precise 16 Bit 540°PAN and 270°TILT
Strobe	0-20T/sec high speed
Display	2.4" TFT LCD display with 4 control buttons
Colors	Rotating wheel with 11 colors plus open
Gobos	Static wheel with 17 Gobos plus open
Prism	8-facet with variable speed and direction
Prism	16-facet with variable speed and direction
Effect	Prism morphing effect between them
Special Effect	7 colour multiray effect filter
Frost	Wash filter with hybrid effect
Front lense	Anti-reflection 136mm
Housing	Flame-retardant plastic
Internal Running Temperature	0 ÷ 40°C
Dimensions (WxDxH)	316,8(W)*235(D)*519(H)mm
Weight	12 kg
Package Dimensions (WxDxH)	365(W)*360(D)*520(H)mm
Package Weight	14,3 kg