

Q-AIR MINI

CENTOLIGHT 4 LED DA 12 W RGBWAUV BATTERY PAR PORTRAIT Q-AIR MINI

PORTRAIT Q-Air Mini is a battery-powered (or mains-powered) PAR, specifically designed for rental applications. You can easily control it by choosing among IR remote control, wired DMX-512 connection, Wireless DMX (by using the **AIRCOM-126**, 2.4GHz Wireless DMX Transceiver for further details), Auto Run, Master/Slave, Sound Active control. The lighting emitting system consists of 4pcs 12W RGBWA+UV 6in1 high-brightness LEDs with a life-span of approximately 50,000 hours. Each LED features a high-quality lens with 15° beam angle and 29° field angle, making this PAR ideal for wash use. The **PORTRAIT Q-Air Mini** has a highly compact housing, and can be fit inside 300x300mm truss to create wonderful wash effect inside the truss structure. The fixture can sit on even and solid floor and work as an up-light. It also has a built-in adjustable tilt support. By pushing the tilt support, the fixture can move up to 25° to wash walls or facades. The high-efficiency lithium battery guarantees a complete charge from zero within about 5 hours, and a working duration ranging from 4 hours (full color mode) to 15 hours (single color mode). The infrared remote control allows remote control of the main functions without the use of DMX.

BAG NOT INCLUDED



PRODUCT DETAILS

Key features

4x 12W RGBWA+UV LED 6in1 high-efficiency and long-life

Beam angle 15°

Field angle 29°

CRI \geq 9090

Wireless 2.4 GHz DMX-512 control

DMX 512 standard wired control RJ45/XLR

Display LED with intuitive interface

Rechargeable Lithium-Ion Battery for up to 15-hour operation

0°-25° adjustable tilt support

Independent Electronic Strobe, 0-20 times per second with adjustable speed.

Specifications

Light sources	4x 12W RGBWA+UV
Beam angle	15°
Field angle	29°
Led average life span	50.000 hours
Control mode	DMX512, Master/Slave, Stand Alone, Wireless DMX, IR Remote Control control
DMX channel	6CH / 10CH
Control panel	LED Display
Power input	100-240VAC 50/60Hz
Power consumption	Max. 55W
Power In connection	5.5mm Input
Battery type	Rechargeable lithium-ion battery pack
Charge time	About 5.0 hours
Battery life	up to 15 hours at running single color
Working temperature	-10°C - 45°C
Charging temperature	0°C - 35°C
IP rating	IP20
Cooling	Natural cooling, silent operation
Housing material	Rigid metal
Housing color	Black
Fixture size (WxDxH)	34 x 134 x 130 mm
Net weight	1.9 kg
Carton size (WxDxH)	180 x 175 x 200 mm
Gross weight	2.5 kg