

TWILIGHT 360 L PRO

3-in-1 Moving Head Fixture

The Centolight **Twilight 360 L Pro** is a compact yet highly versatile 3-in-1 moving head fixture, integrating Beam, Spot, and Wash capabilities in a single professional unit. Powered by a 360W Appotronics white LED, it delivers powerful, uniform, and flicker-free output, making it perfectly suited for broadcast, film, and live performance environments.

The fixture is equipped with a smooth, linear motorized zoom, providing a wide range of beam angles: 4°-32° in Spot mode and 3°-18° in Beam mode, complemented by precise linear focus for accurate and sharp projection. Its advanced effects package includes a 13-color dichroic color wheel, static and rotating gobo wheels with gobo overlay, a 3-facet rotating prism with variable speed and direction, frost filter, and high-speed strobe.

Professional motion control is ensured by 540° pan and 270° tilt with 8/16-bit resolution, scan position memory with automatic repositioning, and reversible pan/tilt functionality. The Twilight 360 L Pro supports a full range of control protocols, including DMX512, RDM, Master/Slave, Auto, and Sound-activated modes.

Designed for demanding professionals, the Twilight 360 L Pro delivers high-quality output, reliability, and exceptional flexibility, making it an ideal solution for a wide variety of lighting applications.



PRODUCT DETAILS

Key features

3-in-1 functionality	Beam, Spot, and Wash modes
1 x 360W White Appotronics LED	
Lamp life span 20.000 Hrs	
High power Lumen output	
Flicker-free operation for broadcast TV and film	
Smooth and linear motorized zoom	
CRI	≥70
Beam Angle	SPOT Mode 4°-32° - Beam mode
Smooth and precise Linear Focus	
540°/270° (8-16 bit) Pan/Tilt	
Scan position memory, auto reposition after unexpected movement	
Reversible Pan/Tilt	
1x Color wheel with 13 dichroic colors plus open	
1x Static gobo wheel with 12 gobos plus open	
1x Rotating gobo wheel with 8 rotatable gobos plus open	
Gobo Overlay	
3-facet circular prism with variable speed and direction	
Frost filter	
0-25Hz shutter/strobe effect with variable speed	
0-100% smooth linear dimming	
DMX Recorder and Edit function integrated	
RDM available (Remote Device Management)	

Specifications

Input Voltage	AC100-240V, 50-60Hz
Power Consumption	395W
Light Source	1x360W, White LED
LED Life span	20.000Hrs
Flicker-free	Yes
Display	LCD Display (reversible)
Color Temperature	9500K (±500)
CRI	≥70
Beam Angle Beam	3°-18°
Beam Angle spot	4°-32°
Pan	540° (8-16 bit) low noise
Tilt	270° (8-16 bit) low noise
Dimmer	0%-100% Dimmer
Strobe	0-25Hz shutter/strobe with variable speed
Ambient Temperature	-25°C - 45°C
DMX Channels	17CH
Control Mode	DMX, Master/Slave, Auto, Sound
DMX Connectors	3-pin XLR Inputs/Outputs
Power Connectors	Powercon Input/Output
Fuse	5A
IP Grade	IP20
Fixture Dimensions (WxDxH)	316,5 x 234,5 x 549 mm(12.46 x 9.23 x 21.61 in.)
Packing Dimensions (WxDxH)	365 x 360 x 520 mm(14.37 x 14.17 x 20.47 in.)
Product Weight	12 kg - 26.45 lbs.
Package Weight	14.3 kg - 31.52 lbs.